



## JetNet 6528Gf-2AC-EU V1.0

### Industrial 28G Full Gigabit Managed Ethernet Switch dual AC Input

16 10/100/1000Base-T(X) 8 100/1000 RJ-45/SFP combo ports  
 4 Gigabit SFP ports  
 Advanced Cyber Security – DHCP Snooping IP Source Guard  
 Dynamic ARP Inspection  
 Redundancy – MSR SuperChain ITU-T G.8032 ERPS  
 USB Firmware upgrade and configuration backup and restore  
 IEEE 1588v2 PTP with HW time stamping

## Facts

### General description

Part number	F00N6528000000
Life cycle status	Active
Warranty	5 Years

### Interface

Total ports number	28
10/100/1000TX ports	16
100/1000M combo	8
Fiber ports	4 x 1000M SFP ports
Console/USB	RS 232/USB
AC power input	2xAC110/220 (90-264V)

### Features

Switch type	L2 Managed
Network redundancy	MSR MultiRing TrunkRing RDH SuperChain ERPS
Broadcast storm protection	Yes
Security	ACL L2/3
DHCP server (Opt82, port based)	Yes

### SW/Protocol

Management	IPv6
RSTP/MSTP	Yes
Traffic priority (QoS)	8 Queues/port
VLAN, P-VLAN, QinQ, GVRP	4k VLANs
IGMP query, snooping, GMRP	Yes
IEEE 802.1AB LLDP network discovery	Yes
IEEE 802.3ad LACP, static trunk	Yes
IEEE 1588 PTP v1/v2	Yes
Jumbo frame/MAC address	9.2Kbytes/16K
Port mirroring	Yes
DDM SFP	Yes
IEEE 802.1x, IP/port security/SSL/HTTPS,SSH/Telnet	Yes
TACACS+, Radius	Yes
Industry protocol (ModBus/TCP,EtherNet/IP)	Yes
SNMP/RMON/Trap	Yes
CLI/Web/Telnet	Yes

### Mechanical

Housing/protection (IP)	IP40
Dimension (HxWxD mm)	44 x 438 x 375
Mounting	Rackmount
Operating temperature	-40~75°C

### Certification

Regulatory/approval	FCC/EN50121-4 /IEEE1613 /IEC61850-3
---------------------	--

