

PRM1505F1-UN30L3-CB0M0A

Fanless Panel PC Rack Mount, 15" LCD monitor, 1600 x 1200, LED 300 nits, Intel® Celeron J6412



Features

- Optional connector type: M12 Metal connectors, MIL-38999, MIL-26482 series connectors
- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Intel® Celeron J6412 processor
- Intel® Elkhart Lake
- Support DDR4-2666/2933/3200MHz, Max. Capacity 32GB
- I/O: 2 x HDMI, 3 x USB 3.0, 3 x USB 2.0, 2 x LAN, 1 x Line-out
- Security support TPM 2.0 onboard IC
- Standard IP66/IP67 models I/O: 1 x HDMI, 2 x USB, 1 x LAN.

Specification

Panel	
Cell Type	TFT LCD
Glass Surface	Black Anti-Glare, low reflection coating
Aspect Ratio	4 : 3
Size	15" viewable diagonal area
Active Area	304.8(H) x 228.6(V) mm
Pixel Pitch	0.1905(H) x 0.1905(V) mm
Native Resolution	1600(H) x 1200(V)
Colors	16.2 M
Brightness	300
Contrast	1000 : 1
Response Time	≤ 20 ms
Viewing Angle (typical)	H. 160°(- 0°~ + 0°) , V. 160°(- 0°~ + 0°)
Light Source	LED backlight, Long life, 35,000 hrs (typ)
Power	
Power Input	Internal power supply with universal / Auto-Sensing, AC90 to 260V, 50/60 Hz
Power Consumption	

System	
CPU	Intel® Celeron J6412
BIOS	UEFI
System / Graphic Chipset	Integrated Intel® UHD Graphics
System Memory	DDR4-2666/2933/3200MHz, Max. up to 32GB
HDD	1*SATA3.0
I/O port	2xHDMI 3xUSB3.0 3xUSB2.0 2xLAN, 1xLin-out
Expansion	1 * M.2 Key-M(NVMe SSD 2280), 1 * M.2 Key-B Slot
Dimensions	
Physical	Please refer to Drawing
Carton	TBD
Operating Condition	
Temperature / Humidity	

Options

Touch	Video Input	Enhanced Panel	Power	Others
Resistive Touch	AV-IN	High Brightness Panel	24V DC-IN	Motion Sensor
Projected Capacitive Touch	AV_Looping	Sunlight Readable	9~36V DC-IN	Light Sensor
Infrared Touch	HDMI / DP	Wide Viewing Angle	48V, 72V DC-IN	VR-knob Dimming
Protected Glass	HD-SDI	Wide Temperature	90V, 125V DC-IN	RS232 Remote On/Off
Optical Bonding		UV Film	110V, 220V DC-IN	Military Connector: MIL 38999
		Anti-Vandal		Metal Connector: M12 / M16
				Stainless 316 Enclosure

Winsonic®

Winsonic Electronics Co., Ltd.

Tel: +886-3-370-4789 Fax: +886-3-370-4722 E-mail: sales@ewinsonic.com

No.290-1, Wen Zhong Rd., Taoyuan City, Taoyuan County 33056, Taiwan (R.O.C.)